

PRODUCT DESCRIPTION

The TelcoBridges Tmedia 1+1 solutions answer service providers' needs for high availability and redundancy. Our Tmedia 1+1 solutions consist of three components:

- A standard Tmedia Unit
- A Tmedia +1 Unit
- And a Tmedia 1+1 patch panel

How the solution works...

When properly installed and configured, the standard Tmedia unit acts as the primary (active) VoIP gateway and the Tmedia +1 unit acts as the secondary (standby). The two devices communicate with each other via the VoIP ports and in the event of product malfunction; traffic is transferred from the active to the standby unit through the patch panel connection, without the need for human intervention.

Tmedia 1+1 solutions ensure redundancy in terms of: power redundancy, packet network redundancy and facility protection.

The Tmedia TMG800 +1 provides a highly available and redundant telecommunications system from 1 to 8 T1/E1s. Just because a deployment may be small doesn't mean it should be less reliable!

Characteristics of the TMG800 & the TMG800+1:

- ✓ 1U VoIP gateway
- ✓ 32 to 256 VoIP channels
- ✓ 1 to 8 T1/E1s
- ✓ Software upgradable by single T1/E1 and 32 VoIP channel increment
- ✓ Single or redundant AC or DC power supplies

IMPORTANT: Tmedia 1+1 solutions are only available for NEW Tmedia products running TMG-CONTROL version 2.6. For more information with regard to TelcoBridges Tmedia 1+1 solution, please contact your certified TelcoBridges Reseller and/or your TelcoBridges Sales Representative.

Ordering information

Standard Tmedia TMG800 Units

Part #	Description
TMG800-1	1 x T1/E1
TMG800-2	2 x T1/E1
TMG800-3	3 x T1/E1
TMG800-4	4 x T1/E1
TMG800-5	5 x T1/E1
TMG800-6	6 x T1/E1
TMG800-7	7 x T1/E1
TMG800-8	8 x T1/E1

Tmedia TMG800+1 Units

Part #	Description
TMG800-1+1	1 x T1/E1
TMG800-2+1	2 x T1/E1
TMG800-3+1	3 x T1/E1
TMG800-4+1	4 x T1/E1
TMG800-5+1	5 x T1/E1
TMG800-6+1	6 x T1/E1
TMG800-7+1	7 x T1/E1
TMG800-8+1	8 x T1/E1

Each configuration is available in either single or redundant AC or DC power.

TelcoBridges Inc.
91 de la Barre, suite 01
Boucherville, QC
J4B 2X6, CANADA

Sales +1.450.655.8993
TB Support +1.866.438.4703

www.telcobridges.com


ILLUSTRATIONS



Standard Tmedia TMG800, 1U VoIP / media gateway front view



Tmedia TMG800+1, 1U VoIP / media gateway front view



1+1 Patch Panel for the Tmedia TMG800 & TMG800+1, 1U, 19" wide rackmount, passive device

Capacity and voice processing

32 to 256 VoIP channels (software upgrade)

PSTN interfaces

1 to 8 T1/E1 (software upgrade)
Independently configurable per port
RJ48C connectors on rear of unit

VoIP interfaces

Dual 100/1000Base-T
RJ45 connectors on rear of unit

Vocoding

Universal codecs: G.711, G.723.1, G.726, G.729ab, T.38 V.17, clear mode (RFC 4040)
Other codecs: G.722.2 (AMR-WB), G.728, G.729eg, iLBC, AMR, EVRC, GSM FR/EFR

Fax/Modem/Data

T.38 fax relay (V.17 and V.34)
Automatic G.711 fallback, modem and data pass-through

DTMF relay

RFC 2833, SIP INFO Method, In-band

Echo cancellation

G.168 echo cancellation
128 ms echo tail on all channels simultaneously

Voice processing

Dynamic and programmable jitter buffer (20 to 200 ms)
Voice activity detection (VAD)
Comfort noise generation (CNG)

Management interfaces

1 RJ45 serial port with RS-232C adapter
Single 100/1000Base-T for OAMP
Supports virtual IP

Signalling (Simultaneous signalling support)

SIP

Supported RFCs: 2327, 2976*, 3261, 3262, 3263, 3264*, 3311*, 3323*, 3325*, 3398, 3515, 3578*, 3764, 3891, 4028, 3581, 3665*, 3666 (*: partial compliance)

SIGTRAN

M2PA, M2UA, M3UA, IUA
SS7 termination and/or relay supported

SS7

Up to 64 x MTP2 links (56, 64, n x 56/64 kbps, HSL)
Multiple redundant MTP2 links
Up to 64 MTP3 originating point codes and linksets
ISUP variants: ITU 92, ITU 97, ANSI 88, ANSI 92, ANSI 95, Q.767, Telcordia 97, ETSIv2, ETSIv3, China, Singapore, UK, Brazil

ISDN PRI

Q.931 ISDN PRI: NI-2, 4ESS, 5ESS, DMS-100, DMS-250, Euro ISDN
ETSI NET5 (France, Germany, UK, China, Hong Kong, Korea), NTT (Japan), Australia

CAS

MFC R2 (standard ITU, Brazil, Mexico)
Customizable protocol script files

TelcoBridges Inc.

91 de la Barre, suite 01, Boucherville, QC, J4B 2X6, CANADA
TB Support +1-866-438-4703, Sales +1-450-655-8993

TMG-CONTROL

Standalone call control

Any to any call routing (TDM-VoIP, TDM-TDM, VoIP-VoIP with transcoding)
Call routing based on: trunk group, calling/called numbers, nature of address, ASR, time of day, load-based, cost-based, TO:, FROM: Request URI, redirect numbers, and other parameters
NPA-NXX routing (100K+ table entries, Excel or CVS file upload)
Route retries, calling/called digit manipulation, Customizable call cause code mapping, Call transfer (REFER, AT&T TR 50075)

H.248 (MEGACO) call control

ITU-T H.248 versions 1 and 2
UDP, SCTP, IPSec transport
DTMF and fax detection
DTMF, call progress tone generation, COT generation
Call quality and inactivity alerts
H.248 control port redundancy (supports virtual IP)

Session management and billing

SIP peer availability polling
RTP inactivity monitoring, RTCP
CDR generation (RADIUS and text file)

OAMP+T

Operation & Administration

Web-based system status and operations
SNMP V2, V3 GET, TRAPs and alarms

Maintenance

Web-based interface for maintenance
Automated system upgrade
System backup, restore and copy

Provisioning

Web-based interface for configuration
Dynamic activation
Dynamic configuration changes

Troubleshooting

Per-call tracing (history and/or live)
Signalling capture tools
SSH command-line interface

Electrical characteristics

Power input (per unit)

90 to 260 VAC, 47 to 63 Hz, -40 to -60 VDC
Redundant power supply option with dual power inputs
Maximum 45W power consumption

Physical characteristics (Dimensions & Weight per unit)

1U, 19" rack mount, 1.75" (44.5mm) H x 17.4" (442mm) W x 11" (279mm) D
10lbs (4.54kg)

Regulatory compliance (UL/CSA 60950, CSA C22.2)

EMC

FCC Part 15:2009, Subpart B, CE Mark (EN55022:2006, Class A, EM60950, EN61000, ETS 300 386)

Environmental

Operating temperature: 0 to +55 °C, 95% re. hum. non-condensing
Storage temperature: -10 to +75 °C, 95% rel. hum. non-condensing
Designed to meet NEBS Level 3, RoHS compliant