

Tmedia™

# TMG3200-STM1

VoIP Gateway



The TelcoBridges Tmedia TMG3200 is our mid-level VoIP gateway. Recognised for its high-capacity and high-performance, the TMG3200-STM-1 is a 1 OC3 / STM1 VoIP gateway that offers high-density in a single box (2U) solution for carriers.

**Product Characteristics:**

- ✓ 2U VoIP gateway,
- ✓ 2016 VoIP channels
- ✓ SIP, SS7, ISDN PRI, E1 CAS R2, T1 CAS R1
- ✓ 1 OC3/STM1 (partial OC3 / STM1 available)
- ✓ Redundant AC or DC power supplies
- ✓ 1+1 Support

Ordering information

Part #	Description
TMG3200-STM1	1 x STM1

Each configuration is available in redundant AC or DC power.

**TelcoBridges Inc.**  
 91 de la Barre, suite 01  
 Boucherville, QC  
 J4B 2X6, CANADA

**Sales** +1.450.655.8993  
**TB Support** +1.866.438.4703

[info@telcobridges.com](mailto:info@telcobridges.com)

[www.telcobridges.com](http://www.telcobridges.com)



Tmedia TMG3200-STM1, 2U VoIP gateway (Front View)



Tmedia TMG3200-STM1 2U VoIP gateway (Back View)

## Capacity and Voice Processing

2,016 VoIP channels

### PSTN interfaces

1 OC3 / STM1 (with Automatic Protection Switching – APS)

Dual RJ48C for BITS or T1 / E1 for signalling

SFP-LC connector type

### VoIP interfaces

Dual 100/1000Base-T, used separately or in bonding RJ45 connectors on rear of unit

### Vocoding

Universal codecs: G.711, G.723.1, G.726, G.729ab, T.38 V.17, clear mode (RFC 4040)

Other codecs: G.722.2 (AMR-WB), G.728, G.729eg, iLBC, AMR, EVRC, GSM FR/EFR, T.38 V.34, QCELP

### Fax/Modem/Data

T.38 fax relay (V.17 and V.34)

Automatic G.711 fallback, modem and data pass-through

Clear mode (RFC 4040)

### DTMF relay

RFC 2833, SIP INFO Method, In-band

### Echo cancellation

G.168 echo cancellation

128 ms echo tail on all channels simultaneously

### Voice processing

Adaptive and programmable jitter buffer (20 to 200 ms)

Voice activity detection (VAD)

Comfort noise generation (CNG)

### Management interfaces

Single 100/1000Base-T for OAMP+T

1 RJ45 serial port with RS-232C adapter

Supports virtual IP

## Signaling

Simultaneously supports any combination or all of the following signaling protocols:

### SIP

Supported RFCs: 2327, 2833, 2976, 3204, 3261, 3262, 3263, 3264, 3311, 3323, 3325, 3326, 3372, 3389, 3398, 3515, 3551, 3555, 3578, 3581, 3665, 3666, 3764, 3891, 4028, 4694, 5806

SIP-I/SIP-T

### SIGTRAN

M2PA, M2UA, M3UA, (IPSP, ASP, SG), IUA

SCTP (raw IP and UDP)

SS7 termination and/or relay supported

Up to 64 M2UA / M2PA links

Up to 20 M3UA peer server processes

### SS7

Up to 64 MTP2 links (56, 64, n x 56/64 kbps, HSL)

Multiple redundant MTP2 links

Up to 64 MTP3 originating point codes and linksets

ISUP variants: ITU 92, ITU 97, ANSI 88, ANSI 92,

ANSI 95, Q.767, Telcordia 97, ETSIv2, ETSIv3,

China, Singapore, UK, Brazil, SPIROU, Japan NTT

SCCP routing and global title transition

### ISDN PRI

Q.931 ISDN PRI: NI-2, 4ESS, 5ESS, DMS-100, DMS-

250, Euro ISDN, ETSI NET5 (France, Germany, UK,

China, Hong Kong, Korea), NTT (Japan), Australia

### CAS

MFC R1 (E&M, loop start user / network side)

MFC R2 (standard ITU, Brazil, Mexico)

Customizable protocol script files

## TMG-CONTROL (Embedded gateway control and management software)

### Embedded Call Control

Call routing based on: trunk group, calling/called numbers digit manipulation, call cause code mapping  
Advance call routing: Priority, load sharing, route retry, Nature of Address (NOA) manipulation  
Programmable call routing: Access and manipulation of call parameters  
RADIUS AAA (supports multiple RADIUS servers)  
NPA-NXX routing (over 100,000 table entries)

### H.248 (MEGACO) Call Control

ITU-T H.248 versions 1 and 2  
UDP, SCTP, IPsec transport  
DTMF and fax tone detection  
Call progress, DTMF and COT tone generation  
Call quality and inactivity alerts  
H.248 control port redundancy (supports virtual IP)

### Session management and billing

SIP peer availability polling  
RTP inactivity monitoring, RTCP  
CDR generation (RADIUS AAA and text file)  
Integrated lawful intercept (ETSI ES 201 671 v.2.1.1)

## OAMP+T (Web-based Interface)

### Operation & Administration

Status, configuration and management GUI  
Configuration change audit logging  
Access and user management  
SNMP V2, V3 GET, TRAPs and alarms

### Maintenance

Automated system upgrade  
System backup, restore and copy  
Extensive system status display  
Multiple software version archive

### Provisioning

Dynamic configuration changes  
Configuration validation  
Multiple configuration archive

### Troubleshooting (TB Analytics)

Call Trace  
Test Call  
TB Sigtrace – Live Signaling Capture  
System Snapshot

## Electrical characteristics (Power Input)

90 to 260 VAC, 47 to 63 Hz, -40 to -60 VDC  
Redundant power supply option with dual power inputs  
Maximum 170W power consumption

## Physical characteristics (Dimensions & Weight)

2U, 19" rack mount, 3.5" (88.9mm) H x 17.4" (442mm) W x 16" (406mm) D  
20lbs (9.1kg)

## Regulatory compliance (UL/CSA 60950, CSA C22.2)

### EMC

FCC Part 15:2009, Subpart B, CE Mark  
(EN55022:2006, Class A, EM60950, EN61000, ETS 300 386)

## Environmental

Operating temperature: 0 to +55 °C, 95% rel. hum. non-condensing  
Storage temperature: -10 to +75 °C, 95% rel. hum. non-condensing  
Designed to meet NEBS Level 3, RoHS compliant