

The TelcoBridges Tdev™ TMP7950 is a high-performance application server device designed for use with the Tdev TMP800 and Tdev TMP6400 computer telephony platforms and is also a key component of the high-capacity Tdev TMP7900 system cluster.

Featuring a powerful quad-core Intel Xeon® 3400-based host with 8GB of RAM, 500GB of RAID-1 storage, the TMP7950 is preconfigured for TB Media Gateway and other value-added service applications developed with the Toolpack™ application development framework. With processing capacity to spare, the TMP7950 is powerful enough to host applications such as softswitches and session border controllers locally, further answering the need for device consolidation and convergence.

For more information on how the Tdev TMP7950 application server can help power your offerings, visit [www.telcobridges.com](http://www.telcobridges.com).

## TMP7950 SPECIFICATIONS

### HARDWARE

#### Standard

CPU: Intel Xeon quad-core X3470 CPU @ 2.93Ghz  
w/ 8MB cache  
Memory: 8 GB RAM DDR3 REG ECC 1333; expandable to 32GB  
Storage: 2 x 500GB SATA hard disk drive/3.5 in/32 MB cache/7200 RPM; configured for RAID-1  
Motherboard: Intel 3400 series / 3420  
USB 2.0 ports: 2 front, 2 rear  
Video: Matrox G200eW 16MB DDR2; 1 VGA port  
Network: 2 rear Ethernet 10/100/1000Mb  
Other ports:  
>1 rear IPMI 2.0 (RJ45) with KVM and dedicated LAN  
>1 rear RS-232 via DB9 connector  
Power supply: 2X 420W AC or 2X 410W DC

#### Optional

Teac 24X CD-ROM Drive or TEAC DVD-ROM Drive  
Sony 3.5" Floppy-Disk Drive  
64-bit 3.3V 1U PCI-X Riser Card

#### Dimensions

2U with dual redundant power supplies  
> 3.5" H (89 mm) x 17.2" W (437 mm) x 17.7" D(450 mm)  
Weight: 36 lbs (16.4 kg)

AC Power: 90 to 260 Volts AC, 47/63 Hz  
DC Power: -40 to -60 Volts DC  
Power Consumption: 375 W fully loaded  
Operating temperature range: 0 to +55 °C, 95% rel. hum. non-condensing  
Storage temperature range: -10 to +75 °C, 95% rel. hum. non-condensing

### OPERATING SYSTEM

> CentOS 5.3 for 64-bit  
> CentOS 5.3 for 32-bit

### APPLICATIONS AND OTHER SOFTWARE

Installers\* for the following:

#### TB Media Gateway™ application (w/source code)

> TDM-to-TDM switching, TDM-to-IP-to-TDM gateway, IP-to-IP hairpinning  
> Transcoding, trunking, call routing, fax relay and other functions  
> Call Detail Records (CDR): user-definable text files and RADIUS  
> High availability

#### Toolpack™ Application Development Tools

> Pre-developed C++ classes (call bridging, call routing, IVR, embedded web-based GUI, voicemail, ODBC database access/RADIUS for CDRs, etc.)

\* Require media gateway / computer telephony platform hardware serial numbers to install

### MANAGEMENT & CONTROL

#### TelcoBridges Element Management System

> Live configuration and software upgrades via HTTP  
> Monitoring via HTTP  
> Configuration of multiple appliances in the same system with a single interface  
> SNMP v2 GET of individual appliance configuration and stats

### REGULATORY COMPLIANCE

EMC	FCC Part 15, EN55022, EN61000, ENV50204
NEBS	Designed to meet Level 3
Safety	CE, UL60950, CSA C22.2 No.60950-1-03
RoHS	Compliant 6/6, Pb Free

