

The TelcoBridges Tmedia™ TMG3200 is a carrier-grade media gateway that meets the needs of service providers looking to drive convergence between TDM and IP networks, replacing multiple devices for signaling, connectivity and IVR with a single device. Offering the ability to add capacity and new functionality via field-upgradable modular hardware components and software license upgrades, the TMG3200 media gateway provides the reliability that leading-edge service providers require as they augment their convergence efforts. A single TMG3200 media gateway provides capacity of 2,048 voice ports and the flexibility to mix and match TDM and IP services such as SS7, ISDN, SIGTRAN, SIP and H.248 across T1/E1/J1, DS-3 and STM-1 interfaces.

Whether sitting at the network core or at the edge, the TMG3200 provides essential media gateway functionality necessary to deliver seamless voice interoperability across TDM and IP networks. Leveraging its integrated media gateway controller or in conjunction with an H.248-compliant softswitch, the TMG3200 offers a low footprint approach to extending services such as media gateway, TDM switching, VOIP hairpinning, transcoding, advanced call routing and fax relay. With separate chipsets for media processing and IVR, and signaling performed in hardware, the TMG3200 media gateway provides full non-blocking capability of up to 2048 channels per device.

Offering the industry-leading highest port density and the lowest operating cost for a media gateway in a 1U form factor, the TMG3200 media gateway easily scales as service uptake increases, with expansion cards for VoIP and TDM. With an average 66% less power consumption than competing products of similar capacity, the TMG3200 media gateway supports the drive by service providers to reduce the environmental impact of their network footprint and increase their profitability and green credentials.

AVAILABLE CONFIGURATIONS

TMG3210 – 8 x T1/E1/J1
TMG3212 – 16 x T1/E1/J1
TMG3214 – 32 x T1/E1/J1
TMG3216 – 48 x T1/E1/J1
TMG3218 – 64 x T1/E1/J1
TMG3220 – 1 x DS-3
TMG3222 – 2 x DS-3
TMG3224 – 3 x DS-3
TMG3230 – 1 x STM-1

Each configuration is available with AC or DC power.

FEATURES & BENEFITS

Density: Supporting up to 64 T1/E1/J1, 3 DS-3 or 1 STM-1 interfaces in a single 1U appliance, the TMG3200 provides up to 2,048 IP voice ports at an industry-leading lowest cost per port. The TMG3200 enables consolidation of multiple devices for signaling, transcoding and IVR into a single device.

Carrier-grade: Architected to exacting industry standards such as NEBS Level 3, the TMG3200 media gateway is designed to meet the need for reliability that service providers and their customers demand.

Flexibility: A network-agnostic platform, the TMG3200 media gateway supports ‘any-to-any’ switching across multiple network interfaces and signaling protocols (SS7, ISDN, CAS R2, SIGTRAN, SIP and H.248) in a single device. It also supports transcoding for all major wireline, wireless and internet codecs.

> Tmedia **TMG3200**



For more information on how the Tmedia TMG3200 media gateway can help transform your offerings, visit www.telcobridges.com.

TMG3200 SPECIFICATIONS

NETWORK INTERFACES

Telephony

4 to 64 T1/E1/J1 TDM ports (hardware & software upgradeable); or
1 to 3 DS-3 (hardware and software upgradeable) + 2 T1/E1/J1 for SS7 signaling or BITS synchronization; or
1 OC3/STM-1 (with Automatic Protection Switching (APS)) + 2 T1/E1/J1 for SS7 signaling or BITS synchronization

Capacity

TDM: 96 to 2048 channels

VoIP: 96 to 2,048 universal ports per device; even more using less complex codecs such as G.711

WAN IP

Dual 100/1000 Base-T for VoIP traffic

LAN

Single 100/1000 Base-T access

MEDIA PROCESSING

PCM Coding A-law to μ -law encoding and conversion

Universal Codecs G.711, G723.1, G.726, G.729ab, T.38 (2048 channels)

DTMF Relay RFC2833, SIP INFO method, in-band

Echo Cancellation G.168 – 128ms tail length on all channels simultaneously

Fax Support T.38 fax relay, Group 3, Fax/modem bypass, G.711 fax fallback

Optional Codecs* AMR, AMR-WB (G.722.2), GSM-FR/GSM-EFR, EVRC/QCELP, G.728, G729eg, iLBC

>Independent dynamic codec selection per channel

APPLICATION SOFTWARE

TB Media Gateway™ application

> TDM-to-TDM switching, TDM-to-IP-to-TDM gateway, IP-to-IP hairpinning
>Transcoding, trunking, call routing, fax relay and other functions
> Call Detail Records (CDR): user-definable text files and RADIUS
>High availability

CALL ROUTING FEATURES

> Fully scriptable (Ruby-based) call routing engine
> CLI (ANI)-based routing and translation
> DID (DNIS)-based routing and translation
> Least cost routing (with time of day/week/year scheduling and other criteria)
> Routing based on Nature of Address (NOA), Numbering Plan Indicator (NPI), and others
> Pre-and post-routing digit translation

REGULATORY COMPLIANCE

EMC	FCC Part 15, EN55022, EN61000, ENV50204
NEBS	Designed to meet Level 3
Safety	CE, UL60950, CSA C22.2 No.60950-1-03

* Additional licenses required.

SIGNALING

ISDN PRI (14+ variants), National ISDN-2, Euro ISDN, DMS100, DMS250, 4ESS, 5ESS, Japan INS-NET1500

SIP: RFC 3261 User Agent, SIP Authentication

CAS R2: scriptable state machine (shipping in Q3 2010)

SS7*: (20+ variants) MTP2, MTP3, SS7/C7 TCAP and ISUP

> Up to 64 SS7 links, up to 2048 CICs, HSL, redundant SS7, single or multiple point codes

SIGTRAN*: M2PA, M2UA, M3UA

H.248*: ITU-T H.248.1 (shipping in Q3 2010)

QUALITY OF SERVICE (VoIP)

Dynamic jitter buffer (adaptive and fixed), Packet loss concealment, Silence Suppression; Denial of Service (DoS) protection for VoIP media

IVR FEATURES

DSP-based plug-in modules; base configuration of 512 channels; field upgradeable to 1024, 1536 and 2048 channels

> Play and record

> Conferencing; up to 132 active participants

> DTMF detection, generation, suppression

> Voice Activity Detection (VAD), Comfort Noise Generation (CNG)

MANAGEMENT INTERFACES

1 DB-9 serial console port with RS-232C adapter

1 100/1000base-T management interface

MANAGEMENT & CONTROL

TelcoBridges Element Management System

> Live configuration and software upgrades via HTTP

> Monitoring via HTTP

> Configuration of multiple appliances in the same system with a single interface

HARDWARE SPECIFICATIONS

Physical Interfaces

PSTN: 4 to 64 T1/E1/J1 via RJ45, 1 to 3 dual BNC DS-3, 1 STM-1 optical or electrical link (with APS). Interface or BITS synchronization

IP: Dual 100/1000 Base-T Ethernet VoIP ports

OAM & Control: 100/1000 Base-T Ethernet port

Dimensions

1U with single power supply

> 1.75" H (44,5 mm) x 17.4" W (442 mm) x 16" D (406 mm)

2U with dual power supplies

> 3.5" H (88.9 mm) x 17.4" W (442 mm) x 16" D (406 mm)

Weight: 1U model @ 15lbs (6.8kg); 2U model @ 20 lbs (9.1 kg)

Environmentals

AC Power: 90 to 260 Volts AC, 47/63 Hz

DC Power: -40 to -60 Volts DC

Power Consumption: 138 W fully loaded

Operating temperature range: 0 to +55 °C, 95% rel. hum. non-condensing

Storage temperature range: -10 to +75 °C, 95% rel. hum. non-condensing