

TMG3200 VoIP Gateway – T1/E1 or DS3 or OC3/STM-1



The TelcoBridges **Tmedia TMG3200** is our medium density carrier-grade VoIP gateway. Recognised for its high performance, the TMG3200 can be ordered to support up to 64 T1/E1 or up to 3 DS3 or 1 OC3/STM-1 into a single box (1U) solution for service providers.

Product Characteristics:

- ✓ 1U VoIP gateway
- ✓ 512 to 2048 VoIP channels with universal codecs
- ✓ TDM interface (ordering option)
 - 16 to 64 T1/E1 or
 - 1 to 3 DS3 or
 - 1 OC3/STM-1 with APS
- ✓ SIP, SIGTRAN, SS7 ISUP, ISDN PRI, E1 CAS R2, T1 CAS R1, H.248
- ✓ Hot-swap redundant power supplies (AC or DC)
- ✓ Optional Tmedia 1+1 solution
- ✓ Software upgradable into a session border controller (SBC) with TDM fallback capabilities
- ✓ Hybrid mode with simultaneous SBC and media gateway functions
- ✓ Performance option for higher CPS rate and support for SIP Registration Forwarding functionality

Tmedia 1+1 Protection Characteristics:

- ✓ Supports all TDM interface types: T1/E1, DS3 or OC3/STM-1
- ✓ Passive solution (no power required)
- ✓ Enables full facility protection (TDM and IP)
- ✓ Active/Standby architecture with two TMG3200 units
- ✓ No single point of failure
- ✓ Five nine's redundancy

Tmedia™ TMG3200 Data Sheet

TelcoBridges Inc.
 91 de la Barre, suite 01
 Boucherville, QC
 J4B 2X6, CANADA

Sales +1.450.655.8993
 TB Support +1.866.438.4703

info@telcobridges.com
www.telcobridges.com

CPS/CAPS

	Standard	Performance Option
SS7-SIP	90/230	140/300
ISDN-SIP	65/195	120/300
SIP-SIP	60/175	180/275

Contact us for other protocol combinations

Capacity and Voice Processing

PSTN interfaces

16 to 64 T1/E1 or
 1 to 3 DS3 or
 1 OC3/STM-1 with APS
 Framing independently configurable per port
 2 BITS interfaces on DS3/OC3/STM-1 units

VoIP interfaces

Up to 4 Ethernet ports 100/1000Base-T
 RJ45 connectors on rear of unit
 Up to 16 different IP addresses
 Ethernet port bonding and 802.1q VLAN support

Vocoding

512 to 2048 VoIP channels with universal codecs
 Universal codecs: G.711, G.723.1, G.726, G.729ab,
 T.38 V.17, clear mode (RFC 4040)
 Other codecs: G.722, G.722.2 (AMR-WB), G.728,
 G.729eg, iLBC, AMR, EVRC, GSM, FR/EFR,
 QCELP, T.38 V.34

Fax/modem/data

T.38 fax relay (V.17 and V.34)
 Automatic G.711 fallback
 Modem and data passthrough, NSE, VBD support
 Clear mode (RFC 4040)

DTMF relay

RFC 2833/4733, SIP INFO method, in-band

Echo cancellation

G.168 echo cancellation
 128 ms echo tail on all channels simultaneously

Voice processing

Adaptive and programmable jitter buffer (20 to 200 ms)
 Voice activity detection (VAD)
 Comfort noise generation (CNG)

Voice recording and announcement playback

Up to 2048 channels (using optional IVR mezzanine or
 specially licensed VoIP channels)

Signaling

Simultaneously supports any combination or all of the
 following signaling protocols:

SIP

Supported RFCs: 2327, 2833, 2976, 3204, 3261, 3262,
 3263, 3264, 3311, 3323, 3325, 3326, 3372, 3389,
 3398, 3515, 3551, 3555, 3578, 3581, 3665, 3666,
 3764, 3891, 4028, 4694, 4733, 5806

SIP-I/SIP-T

Extensive SIP header manipulation
 SIP registration Forwarding¹

SS7

Up to 64 MTP2 links (56, 64, n x 56/64 kbps) or
 2 x HSL
 Multiple redundant MTP2 links
 Up to 64 originating point codes and 256 linksets
 Up to 256 destination point codes
 ISUP variants: ITU 92, ITU 97, ANSI 88, ANSI 92,
 ANSI 95, Q.767, Telcordia 97, ETSI v3, China,
 Singapore, UK, SPIROU, Japan NTT, Russia

SIGTRAN

M2PA, M2UA, M3UA (IPSP, ASP, SG), IUA
 SCTP (raw IP and UDP)
 SS7 termination and/or relay supported
 Up to 64 M2UA / M2PA links
 Up to 64 M3UA peer server processes

ISDN PRI

Q.931 ISDN PRI (user and network side)
 ISDN variants: NI-2, 4ESS, 5ESS, DMS-100,
 DMS-250, Euro ISDN ETSI NET5 (France,
 Germany, UK, China, Hong Kong, Korea), Euro
 Numeris (VN6), NTT (Japan), Australia
 ISDN NFAS with D-channel backup

CAS

MF R1 (including E&M, loop start, ground start)
 MF R2 (including standard ITU, Brazil, Mexico,
 Venezuela)
 Customizable script files to implement any CAS variant

¹ Requires Performance option

High Availability & Redundancy

Power supply redundancy
 IP port redundancy
 Self-recovery software
 Fault tolerant software
 MTP2/SS7 links redundancy

Tmedia 1+1 solution (optional)

The Tmedia 1+1 solution extends the high-availability and redundancy features of the TMG3200

VoIP gateway redundancy (active/standby)
 Full capacity protection (TDM and IP)
 Configuration database redundancy
 Seamless software upgrade
 M3UA/MTP3/ISUP redundancy

Tmedia 1+1 solution consists of:

- 1 active unit and 1 standby unit
- Up to 2 units 1+1 Patch Panel(s)

1+1 Patch Panels are passive (no power required)

Tctrl (Call Control)

Toolpack framework call control

Call routing based on: trunk group, calling/called numbers (with digit manipulation) and/or various other protocol information/headers.
 Customizable routing including priority-based, load-balancing, black listing, call limiting, route retries, etc.
 Customizable call cause code mapping
 Programmable call routing: Access and manipulation of call parameters (SIP, SS7 and ISDN), including Nature of Address (NOA)
 RADIUS authentication and authorization (supports multiple RADIUS servers)
 NPA-NXX routing (over 5 million records)
 SIP-based local number portability and CNAM lookup

H.248 (MEGACO) call control

ITU-T H.248 versions 1 and 2
 UDP, SCTP, IPsec transport
 DTMF and fax detection
 Call progress, DTMF and COT tone generation
 Call quality and inactivity alerts
 H.248 control port redundancy (supports virtual IP)

Session management and billing

SIP peer availability polling
 RTP inactivity monitoring, RTCP
 CDR generation (RADIUS and/or csv files)
 Integrated lawful intercept (ETSI ES 201 671 v.2.1.1)

Software upgradable to SBC

Back-to-back user agent (B2BUA)
 Maximum signaling/media sessions: 3000
 Maximum transcoding sessions: 2744
 Topology hiding
 Line-rate DOS/DDOS protection (64 bytes packets)
 Rogue RTP detection
 Dynamic blacklisting
 Access control list
 Session admission control
 Session bandwidth control
 TDM fallback capabilities

OAMP+T

Operations & Administration

Provisioning, management and status GUI
 CLI and configuration file machine-to-machine interface (RESTful)
 Configuration change audit logging
 Access, user and privilege management
 SNMP V2, V3 GET, TRAPs (alarms)
 Extensive SNMP call statistics MIBs

Management

1 Ethernet control ports 100/1000Base-T
 1 USB Type B serial port
 1 RJ45 RS232 serial port
 GUI-based and CLI system upgrade
 GUI-based configuration copy, backup and restore
 Storage for multiple software versions
 Storage for multiple configuration files
 Extensive system status display

Provisioning

Non-service affecting configuration changes
 Offline configuration validation
 Multiple configuration files archive
 Northbound API (RESTful) for automated provisioning

Network Analytics (TB Analytics)

Live call trace with protocol information and ladder diagrams
 Live test call with media playback and recording
 TB Sigtrace – Protocol signaling capture into pcap files
 Media call recording (scriptable for calling and called numbers)

Maintenance

Replaceable fan filters

Dimensions & Weight

TMG3200

1U, 19" rackmount
 1.75" (44.5 mm)H x 16.9" (429 mm)W x 16" (406 mm)D
 14.5 lbs (6.6 kg)

TMG3200 1+1 patch panels

1U, 19" rackmount
 1.75"(44.5 mm)H x 16.9"(429 mm)W x 5.25"(133 mm)D
 3.4 lbs (1.6 kg)

Regulatory Compliance

Safety

CAN.CSA C22.2
 EN 60950-1:2005
 EN 60950-1:2006

EMC

FCC Part 15:2013, Subpart B,
 CE Mark (EN55022:2010, Class A, EN61000, ETSI
 EN 300 386)

Electrical Characteristics

90 to 260 VAC, 47 to 63 Hz or -36 to -72 VDC
 Hot-swap redundant power supply (AC or DC)
 Maximum 138W power consumption

Environmental

Operating temperature:
 0 to +70 °C, 95% rel. hum. non-condensing
 Storage temperature:
 -10 to +85 °C, 95% rel. hum. non-condensing
 Designed to meet NEBS Level 3
 RoHS compliant



Tmedia TMG3200 (front view)



Tmedia TMG3200-TE AC (rear view)



Tmedia TMG3200-DS3 AC (rear view)



Tmedia TMG3200-STM1 AC (rear view)



Tmedia TMG3200-TE 1+1, Patch Panel (front view)



Tmedia TMG3200-DS3 1+1, Patch Panel (front view)



Tmedia TMG3200-STM1 1+1, Patch Panel (front view)

© 2017 TelcoBridges Inc. All rights reserved.
 The TelcoBridges logo is a registered trademark of TelcoBridges Inc.
 This document and any products or functionality it describes are
 subject to change without notice.
 Please contact TelcoBridges for additional information and updates.