



TMG800 VoIP Gateway - 1 to 16 T1/E1



The TelcoBridges **Tmedia TMG800** is our low density carrier-grade VoIP gateway.

Software upgradeable from 1 to 16 T1/E1, the TMG800 is the most cost-effective VoIP gateway solution for service providers that is currently available on the market.

Product Characteristics:

- ✓ 1U VoIP gateway
- ✓ 32 to 512 VoIP channels with universal codecs
- ✓ 1 to 16 T1/E1
- ✓ SIP, SIGTRAN, SS7 ISUP, ISDN PRI, E1 CAS R2, T1 CAS R1, H.248
- ✓ Software upgradeable by single T1/E1 and 32 VoIP channel increments
- ✓ Dual feed redundant power supplies (AC or DC)
- ✓ Tmedia 1+1 solution option

Tmedia™
TMG800 Data Sheet

TelcoBridges Inc.
91 de la Barre, suite 01
Boucherville, QC
J4B 2X6, CANADA

Sales +1.450.655.8993
TB Support +1.866.438.4703

info@telcobridges.com

www.telcobridges.com



Tmedia TMG800 1U VoIP gateway, front and rear view (dual AC power input shown)

Capacity and Voice Processing

32 to 512 VoIP channels with universal codecs

PSTN interfaces

1 to 16 T1/E1 (software upgradeable)
Configurable per port for T1 or E1
RJ48C connectors on rear of unit
Port status LEDs

VoIP interfaces

Up to 6 Ethernet ports 100/1000Base-T
RJ45 connectors on rear of unit
Up to 16 different IP addresses
Ethernet port bonding and 802.1q VLAN support

Vocoding

Universal codecs: G.711, G.723.1, G.726, G.729ab, T.38
V.17, clear mode (RFC 4040)
Other codecs: G.722, G.722.2 (AMR-WB), G.728, G.729eg,
iLBC, AMR, EVRC, GSM FR/EFR, QCELP, T.38 V.34

Fax/modem/data

T.38 fax relay (V.17 and V.34)
Automatic G.711 fallback, modem and data passthrough,
NSE, VBD support
Clear mode (RFC 4040)

DTMF relay

RFC 2833/4733, SIP INFO method, in-band

Echo cancellation

G.168 echo cancellation
128 ms echo tail on all channels simultaneously

Voice processing

Adaptive and programmable jitter buffer (20 to 200 ms)
Voice activity detection (VAD)
Comfort noise generation (CNG)

Voice recording and announcement playback (optional)

Up to 512 optional channels

High Availability & Redundancy

Power supply redundancy
IP port redundancy
Self-recovery software
MTP2/SS7 links redundancy

Tmedia 1+1 solution (optional)

The Tmedia 1+1 solution extends the high-availability and redundancy features of the TMG800

VoIP gateway redundancy (active/standby)
Full capacity protection (TDM and IP)
Configuration database redundancy
Seamless software upgrade
Fault tolerant software
M3UA/MTP3/ISUP redundancy

Tmedia 1+1 solution consists of:

1 active Tmedia unit and 1 standby Tmedia unit
1 or 2 Tmedia 1+1 Patch Panel(s)
1+1 Patch Panels are passive (no power required)



Tmedia 1+1 solution schematic

Signaling

Simultaneously supports any combination or all of the following signaling protocols:

SIP

Supported RFCs: 2327, 2833, 2976, 3204, 3261, 3262, 3263, 3264, 3311, 3323, 3325, 3326, 3372, 3389, 3398, 3515, 3551, 3555, 3578, 3581, 3665, 3666, 3764, 3891, 4028, 4694, 4733, 5806

SIP-I/SIP-T

SIP header manipulation

SS7

Up to 64 MTP2 links (56, 64, n x 56/64 kbps) or 2 x HSL

Multiple redundant MTP2 links

Up to 64 originating point codes and 256 linksets

Up to 256 destination point codes

ISUP variants: ITU 92, ITU 97, ANSI 88, ANSI 92, ANSI 95, Q.767, Telcordia 97, ETSIv2, ETSIv3, China, Singapore, UK, SPIROU, Japan NTT, Russia

SIGTRAN

M2PA, M2UA, M3UA (IPSP, ASP, SG), IUA

SCTP (raw IP and UDP)

SS7 termination and/or relay supported

Up to 64 M2UA / M2PA links

Up to 20 M3UA peer server processes

ISDN PRI

Q.931 ISDN PRI (user and network side)

ISDN variants: NI-2, 4ESS, 5ESS, DMS-100, DMS-250, Euro

ISDN ETSI NET5 (France, Germany, UK, China, Hong Kong,

Korea), Euro Numeris (VN6), NTT (Japan), Australia

ISDN NFAS

CAS

MF R1 (including E&M, loop start, ground start)

MF R2 (including standard ITU, Brazil, Mexico, Venezuela)

Customizable script files to implement any CAS variant

TMG-CONTROL (Call Control)

Embedded call control

Call routing based on: trunk group, calling/called numbers (with digit manipulation) and/or various other protocol information/headers.

Customizable routing including priority-based, load-balancing, black listing, call limiting, route retries, etc.

Customizable call cause code mapping

Programmable call routing: Access and manipulation of call parameters (SIP, SS7 and ISDN), including Nature of Address (NOA)

RADIUS authentication and authorization (supports multiple RADIUS servers)

NPA-NXX routing (over 5 million records)

SIP-based local number portability and CNAM lookup

H.248 (MEGACO) call control

ITU-T H.248 versions 1 and 2

UDP, SCTP, IPSec transport

DTMF and fax detection

Call progress, DTMF and COT tone generation

Call quality and inactivity alerts

H.248 control port redundancy (supports virtual IP)

Session management and billing

SIP peer availability polling

RTP inactivity monitoring, RTCP

CDR generation (RADIUS and/or csv files)

Integrated lawful intercept (ETSI ES 201 671 v.2.1.1)

OAMP+T (Web-Based Interface)

Operations & Administration

Configuration, management and status GUI

CLI and configuration file machine-to-machine interface

Configuration change audit logging

Access, user and privilege management

SNMP V2, V3 GET, TRAPs (alarms)

Extensive SNMP call statistics MIBs

Management

- 2 Ethernet ports 100/1000Base-T
- 1 USB Type B serial port
- GUI-based system upgrade
- GUI-based configuration copy, backup and restore
- Storage for multiple software versions
- Storage for multiple configuration files
- Extensive system status display

Provisioning

- Non-service affecting configuration changes
- Offline configuration validation
- Multiple configuration files archive
- Machine-to-machine configuration interface

Troubleshooting (TB Analytics)

- Live call trace with protocol information and ladder diagram
- Live test call with media playback and recording
- TB Sigtrace – Protocol signaling capture into pcap files
- Media call recording (scriptable for calling and called numbers)

Maintenance

- Replaceable fan filters

Dimensions & Weight

1U, 19" rackmount
 1.75" (44.5 mm) H x 16.9" (429 mm) W x 16" (406 mm) D
 14 lbs (6.4 kg)

1+1 patch panel (8 T1/E1)

1U, 19" rack mount
 1.75" (44.5 mm) H x 16.9" (429 mm) W x 5.25" (133 mm) D
 3.4 lbs (1.6 kg)

Electrical Characteristics

- 90 to 260 VAC, 47 to 63 Hz or -36 to -72 VDC
- Dual feed redundant power supplies (AC or DC)
- Maximum 70W power consumption

Regulatory Compliance

Safety

- CAN.CSA C22.2
- EN 60950-1:2005
- EN 60950-1:2006

EMC

- FCC Part 15:2013, Subpart B,
- CE Mark (EN55022:2010, Class A, EN61000, ETSI EN 300 386)

Environmental

- Operating temperature:
 0 to +70 °C, 95% rel. hum. non-condensing
- Storage temperature:
 -10 to +85 °C, 95% rel. hum. non-condensing
- Designed to meet NEBS Level 3
- RoHS compliant

Mean Time Between Failure (MTBF)

MTBF of 400,000+ hours for the entire system



Tmedia TMG800 1+1 Patch Panel, (front view)

© 2015 TelcoBridges Inc. All rights reserved.
 The TelcoBridges logo is a registered trademark of TelcoBridges Inc.
 This document and any products or functionality it describes are subject to change without notice.
 Please contact TelcoBridges for additional information and update

