

ORDERING INFORMATION

Part #	Description
TMG3200-TE-16	16 x T1/E1
TMG3200-TE-32	32 x T1/E1
TMG3200-TE-48	48 x T1/E1
TMG3200-TE-64	64 x T1/E1

Each configuration is available with redundant AC or DC power.

The TelcoBridges Tmedia™ TMG3200 is our mid-level VoIP gateway.

Notorious for its **high-capacity** and **high-performance**, the TMG3200-TE is an 16 to 64 T1/E1 VoIP gateway that offers the industry's **highest density in a single box (2U)** solution.

Characteristics of the TMG3200-TE:

- ✓ 2U VoIP gateway
- ✓ 512 to 2048 VoIP channels
- ✓ 16 to 64 T1/E1s
- ✓ Simple field upgrade by 16 T1/E1 and 512 VoIP channel increment
- ✓ Redundant AC or DC power supplies

For more information on the Tmedia TMG3200-TE visit www.telcobridges.com.

Tmedia TMG3200-TE, front view



Tmedia TMG3200-TE, rear view



Capacity and voice processing

512 to 2,048 VoIP channels (simple field upgrade)

PSTN interfaces

16 to 64 T1/E1 (simple field upgrade)
Independently configurable per port
SCSI connectors to RJ48C patch panel

VoIP interfaces

Dual 100/1000Base-T
RJ45 connectors on rear of unit

Vocoding

Universal codecs: G.711, G.723.1, G.726, G.729ab, T.38
Other codecs: G.722.2 (AMR-WB), G.728, G.729eg, iLBC, clear mode (RFC 4040)

Fax/Modem/Data

T.38 fax relay (V.17 and V.34)
Automatic G.711 fallback
Modem and data pass-through

DTMF relay

RFC 2833, SIP INFO Method, In-band

Echo cancellation

G.168 echo cancellation
128 ms echo tail on all channels simultaneously

Voice processing

Dynamic and programmable jitter buffer (20 to 200 ms)
Voice activity detection (VAD)
Comfort noise generation (CNG)

Management interfaces

Dual 100/1000 Base-T for OAMP

Signalling

Simultaneous signalling support:

SIP

Supported RFCs: 2327, 2976, 3261, 3262, 3263, 3264, 3311*, 3323*, 3325*, 3398, 3515*, 3578*, 3764, 3891, 4028 (*: partial compliance)

SIGTRAN

M2PA, M2UA, M3UA, IUA
SS7 termination and/or relay supported

SS7

Up to 64 x MTP2 links (56, 64, n x 56/64 kbps, HSL)
Multiple redundant MTP2 links
Up to 64 MTP3 originating point codes and linksets
ISUP variants: ITU 92, ITU 97, ANSI 88, ANSI 92, ANSI 95, Telcordia 97, ETSIv2, ETSIv3, China, Singapore, UK Brazil

ISDN PRI

Q.931 ISDN PRI: NI-2, 4ESS, 5ESS, DMS-100, DMS-250, Euro ISDN ETSI NET5 (France, Germany, UK, China, Hong Kong, Korea), NTT (Japan), Australia

CAS

MFC R2 (standard ITU, Brazil)
Customizable protocol script files

TMG-CONTROL

Standalone call control

Any to any call routing (TDM-VoIP, TDM-TDM, VoIP-VoIP with transcoding)
Call routing based on: trunk group, calling/called numbers, nature of address, ASR, time of day, load-based, cost-based, TO:, FROM: Request URI, redirect numbers, and other parameters
NPA-NXX routing (100k+ table entries, Excel or CVS file upload)
Route retries
Call transfer (REFER, AT&T TR 50075)

H.248 (MEGACO) call control

ITU-T H.248 versions 1 and 2
UDP, SCTP, IPSec transport
DTMF and fax detection
DTMF, announcements and call progress tone generation
Call quality and inactivity alerts

Session management and billing

SIP peer availability polling
RTP inactivity monitoring
CDR generation (RADIUS and text file)

OAMP+T

Operation & Administration

Web-based system status and operations
SNMP v2 GET, TRAPs and alarms
Dynamic configuration changes

Maintenance

Web-based interface for maintenance
Automated system upgrade
System backup, restore and copy

Provisioning

Web-based interface for configuration
Dynamic activation

Troubleshooting

Per-call tracing (history and/or live)
Signalling capture tools
SSH command-line interface

Electrical characteristics

Power input

90 to 260 VAC, 47 to 63 Hz
-40 to -60 VDC
Redundant power supply with dual power inputs
Maximum 138W power consumption

Physical characteristics (*Dimensions & Weight*)

2U, 3.5" (88.9mm) H x 17.4" (442mm) W x 16" (406mm) D
20lbs (9.1kg)

Regulatory compliance (UL/CSA 60950, CSA C22.2)

EMC : FCC Part 15:2009, Subpart B, CE Mark (EN55022:2006, Class A, EM60950, EN61000, ETS 300 386)

Environmental

Operating temperature: 0 to +55 °C, 95% re. hum. non-condensing
Storage temperature: -10 to +75 °C, 95% rel. hum. non-condensing
NEBS Level 3 compliant
RoHS compliant